

A34109 PCT USA (067515.0132)

### Claims

1. (Previously Presented) A common subscriber managing apparatus for use in an Internet Protocol network in which a circuit network for voice and a packet network for data are integrated, the apparatus comprising:

first portable user terminating means satisfying media voice or data standard supported in the network;

wireless interfacing means for controlling wireless resources of said user terminating means and wireless traffic, controlling handoff, realigning data from and to the packet network based on a request of said user terminating means to have interfacing condition, providing the realigned data to said user terminating means, and transferring the media to a second user terminating means;

call controlling means for controlling a call between the wireless interfacing means and common subscriber managing means; and

common subscriber managing means for providing Security Association setup function for voice processing and commonly managing mobility management, Quality of Service, authentication and authorization management, accounting management and service management functions for said first user terminating means by using a common subscriber database, wherein the common subscriber managing means uses a first protocol for mobility management and service management and a second protocol for Quality of Service management, for authentication and accounting management as application layer protocol, and for constructing protocol stack for implementing common subscriber management function.

A34109 PCT USA (067515.0132)

2. (Original) The apparatus as recited in claim 1, further comprising service managing means for performing the service management functions.

3. (Canceled)

4. (Previously Presented) The apparatus as recited in claim 2, wherein said common subscriber managing means uses User Datagram Protocol/Transmission Control Protocol as a transmission layer protocol.

5. (Previously Presented) The apparatus as recited in claim 2, wherein said common subscriber managing means uses IP (Internet Protocol) as a network layer protocol.

6. (Previously Presented) A method for managing commonly subscribers for use in an Internet Protocol network in which a circuit network for voice and a packet network for data are integrated, the method comprising the steps of:

(a) modeling to provide, by a server, mobility management, Quality of Service, authentication and authorization management, accounting management and service management for a roaming terminal by using a common subscriber database for all Internet Protocol service, wherein, during step (a), the method uses a first protocol for mobility management and the service management and a second protocol for Quality of Service management, for authentication and accounting management as application layer protocol, and for constructing protocol stack for implementing common subscriber management function; and

(b) setting SA (Security Association) function for voice processing by setting up a call between an ALL-IP visiting network and a home network by the server and commonly managing

A34109 PCT USA (067515.0132)

the mobility management, the QoS, the authentication and authorization management, the accounting management and the service management.

7. (Canceled)

8. (Original) The method as recited in claim 7, wherein, during step (a), the method uses User Datagram Protocol/Transmission Control Protocol as a transmission layer protocol.

9. (Original) The method as recited in claim 7, wherein, during step (a), Internet Protocol is used as a network layer protocol.

10. (Previously Presented) The method as recited in claim 6, wherein the step (b) includes:

(i) when an originating Radio Access Network (RAN\_0) transmits a call setup request message to an originating Call Control Function (CCF\_0), transferring an access request message from the CCF\_0 to a visiting common subscriber server (CSS\_V);

(ii) searching a Home CSS (CSS\_H) by the CSS\_V for proxy processing of a corresponding message;

(iii) obtaining by the CSS\_V a Temporary Local Directory Number and location information of a terminating subscriber from a terminating Call Control Function (CCF\_T) to transfer said Temporary Local Directory Number TLDN and the said location information to said CSS\_H;

A34109 PCT USA (067515.0132)

(iv) transferring a Security Association setup message from said CSS\_V and said CSS\_H to said RAN\_O and the location information, respectively, and setting said Security Association between said RAN\_O and said location information;

(v) when said CSS\_V receives a access response message, transferring a path reset request message for call setup for the said location information from said CCF\_O to said RAN\_O; and

(vi) setting up a call between the Internet Protocol visiting network and the home network by transferring the call setup request message from said location information to the RAN\_T and transferring a call setup completion message from said location information to said RAN\_O.

11. (Original) The method as recited in claim 6, wherein step (b) includes:

(i) when an originating Radio Access Network (RAN\_O) transmits a call setup request message to an originating Call Control Function (CCF\_O), transferring an access request message from said CCF\_O to a visiting common subscriber server (CSS\_V);

(ii) searching a Home CSS (CSS\_H) by the CSS\_V for proxy processing of a corresponding message;

(iii) obtaining through said CSS\_H a Temporary Local Directory Number (TLDN) and location information (RAN\_T) of a terminating subscriber from a terminating Call Control Function (CCF\_T) to said CCF\_T;

(iv) requesting a service by said CSS\_H and obtaining service related profile from a server corresponding to said service by the CSS\_H;

(v) providing said TLDN, said RAN\_T IP address, and service related information for the terminating subscriber, from said CSS\_H to said CSS\_V;

A34109 PCT USA (067515.0132)

(vi) transferring a Security Association setup message from said CSS\_V and said CSS\_H to said RAN\_O and said RAN\_T, respectively, and setting said Security Association between said RAN\_O and said RAN\_T;

(vii) when said CSS\_V receives an access response message, transferring a path reset request message for call setup for said RAN\_T from said CCF\_O to said RAN\_O; and

(viii) setting up a call between the Internet Protocol visiting network and the home network by transferring said call setup request message from said RAN\_O to said RAN\_T and transferring a call setup completion message from said RAN\_T to said RAN\_O.

12. (Previously Presented) The method as recited in claim 6, wherein step (b) includes:

(i) when an originating Radio Access Network (RAN\_O) transmits a call setup request message to an originating Call Control Function (CCF\_O), transferring an access request message from said CCF\_O a visiting common subscriber server (CSS\_V);

(ii) searching a Home common subscriber service (CSS\_H) by said CSS\_V for proxy processing of a corresponding message;

(iii) using said CSS\_H for requesting a service and mobility to a service server,

(iv) providing a Temporary Local Directory Number (TLDN) and location information (RAN\_T IP address) of a terminating subscriber from said CSS\_H to said CSS\_V;

(v) transferring a Security Association setup message from said CSS\_V and said CSS\_H to said RAN\_O and said RAN\_T, respectively, and setting said Security Association between said RAN\_O and said RAN\_T;

(vi) when said CSS\_V receives a access response message, transferring a path reset request message for call setup for said RAN\_T from said CCF\_O to said RAN\_O; and

A34109 PCT USA (067515.0132)

(vii) setting up a call between the Internet Protocol visiting network and the home network by transferring the call setup request message from said RAN\_O to said RAN\_T and transferring a call setup completion message from said RAN\_T to said RAN\_O.

13. (Original) In an Internet Protocol network having a processor, a computer readable recording medium for recording a program for implementing the functions of:

(a) modeling to provide, by a server, mobility management, Quality of Service, authentication and authorization management, accounting management and service management functions for a roaming terminal by using a common subscriber database for Internet Protocol service; and

(b) setting a Security Association function for voice processing by setting up a call between an Internet Protocol visiting network and a home network by the server and commonly managing the mobility management, Quality of Service, authentication and authorization management, accounting management, and service management functions.

14 -36. Cancelled.